









Product	Photo	Items	Specification ( Warranty : 2 years)									
			Color	Power	Material	Voltage and Power Source	Size	Cutout Size	chip	Color Temperature	CRI	Luminous
Spot Lights												
Track Lights default with EPISTAR Chip, COB		HY-TL-01	Black/White	30W	Aluminum+Light Pipe+reflection cup	AC85-265V; 50/60Hz; constant current, isolated power, with fuse and piezoresistor	Ø95mm L146mm Beam Angle24°		variety for your choose	3000K 4000K 6000K	>80	90lm/W
		HY-TL-02	Black/White	30W	Aluminum+Light Pipe+reflection cup	AC85-265V; 50/60Hz; constant current, isolated power, with fuse and piezoresistor	Ø95mm L135mm Beam Angle24°		variety for your choose	3000K 4000K 6000K	>80	85 (lm/W)
		HY-TL-03	Black	7W,10W	Aluminum+Light Pipe+reflection cup+Flame-retardant base	AC85-265V; 50/60Hz; constant current, isolated power, with fuse and piezoresistor	Ø60mm L100mm Beam Angle24°		variety for your choose	3000K 4000K 6000K	>80	85 (lm/W)
		HY-TL-04	Black/White	20W	Aluminum+Light Pipe+reflection cup	AC85-265V; 50/60Hz; constant current, isolated power, with fuse and piezoresistor	Ø80mm L200mm 4 kinds of aperture size, swithable		variety for your choose	3000K 4000K 6000K	>80	90lm/W
		HY-TL-05	Black	7W	Aluminum+Light Pipe+reflection cup	AC85-265V; 50/60Hz; constant current, isolated power, with fuse and piezoresistor	Ø60mm L115mm		variety for your choose	3000K 4000K 6000K	>80	85 (lm/W)
Recessed LED Lights default with EPISTAR Chip, COB		HY-RL-01	Black/White	20W	Aluminum+Light Pipe+reflection cup	AC85-265V; 50/60Hz; constant current, isolated power, with fuse and piezoresistor	88.9mm*127mm	140mm	variety for your choose	3000K 4000K 6000K	>80	85lm/W
		HY-RL-02	Black/White	5W,7W,10W	Cold forging aluminum	AC85-265V; 50/60Hz; constant current, isolated power, with fuse and piezoresistor	Ø90mm H98mm Beam Angle24°	80mm	variety for your choose	3000K 4000K 6000K	>80	80 (lm/W)
		HY-RL-03	Black/White	12W	Lathe aluminum	AC85-265V; 50/60Hz; constant current, isolated power, with fuse and piezoresistor	Ø95mm H80mm Beam Angle24°	85mm	variety for your choose	3000K 4000K 6000K	>80	80 (lm/W)
		HY-RL-04	Black/White	6W	Cold forging aluminum	AC85-265V; 50/60Hz; constant current, isolated power, with fuse and piezoresistor	Ø92mm H90mm Beam Angle24°	70mm	variety for your choose	3000K 4000K 6000K	>80	80 (lm/W)
		HY-RL-05	Black/White	12W	Seiko aluminum	AC85-265V; 50/60Hz; constant current, isolated power, with fuse and piezoresistor	Ø100mm H72mm Beam Angle24°	100mm	variety for your choose	3000K 4000K 6000K	>80	80 (lm/W)
		HY-RL-06	Black/White	10W	Aluminum	AC85-265V; 50/60Hz; constant current, isolated power, with fuse and piezoresistor	L125XW125XH110(mm) Beam Angle15°	L110mm*W110mm	variety for your choose	3000K 4000K 6000K	>80	80 (lm/W)
		HY-RL-07	Black/White	12W,20W	Cold forging aluminum	AC85-265V; 50/60Hz; constant current, isolated power, with fuse and piezoresistor	L170XW93XH95 (mm) Beam Angle 24°	L152mm*W78mm	variety for your choose	3000K 4000K 6000K	>80	80 (lm/W)
		HY-RL-08	Black/White	20W	Aluminum	AC85-265V; 50/60Hz; constant current, isolated power, with fuse and piezoresistor	L225XW130XH130 (mm) Beam Angle 15°	L200mm*W105mm	variety for your choose	3000K 4000K 6000K	>80	85 (lm/W)
		HY-RL-09	Gold	10W	Cold forging aluminum	AC85-265V; 50/60Hz; constant current, isolated power, with fuse and piezoresistor	Ø89mm H110mm Beam Angle24°	78mm	variety for your choose	3000K 4000K 6000K	>80	80 (lm/W)
		HY-RL-10	White	12W	Cold forging aluminum	AC85-265V; 50/60Hz; constant current, isolated power, with fuse and piezoresistor	Ø90mm H110mm Beam Angle 60°	80mm	variety for your choose	3000K 4000K 6000K	>80	80 (lm/W)
LED Wall Washer												
Wall Washer Light		HY-WWL-01	silver gray/black	18W	Aluminum	AC220V; 50/60Hz; constant current, isolated power, with fuse and piezoresistor	1200mm		cooper stent	3000K 4000K 6000K	>70	80lm/W
Downlight												
Downlight		HY-DL-01	White	18W	Die cast Aluminum	AC85-265V; 50/60Hz; constant current, isolated power, with fuse and piezoresistor	76*100mm	95mm	variety for your choose	3000K 4000K 6000K	>70	80lm/W
		HY-DL-02	Black/White	7W,24W	Die cast Aluminum	AC85-265V; 50/60Hz; constant current, isolated power, with fuse and piezoresistor	Ø80*H90/Ø115X155 (mm) Beam Angle120°		variety for your choose	3000K 4000K 6000K	>80	80lm/W
		HY-DL-03	Rose gold/White	7W	Cold forging aluminum	AC85-265V; 50/60Hz; constant current, isolated power, with fuse and piezoresistor	Ø93xH78 (mm) Beam Angle24°	75mm	variety for your choose	3000K 4000K 6000K	>80	85lm/W
		HY-DL-04	White	9W,15W	Die cast Aluminum	AC85-265V; 50/60Hz; constant current, isolated power, with fuse and piezoresistor	Ø115xH50 (mm) Beam Angle120°	95mm	variety for your choose	3000K 4000K 6000K	>80	85lm/W

		HY-DL-05	White	7W,12W	ADC-12 High quality aluminum	AC85-265V; 50/60Hz; constant current, isolated power, with fuse and piezoresistor	Ø90xH70 (mm) Beam Angle120°	76mm	variety for your choose	3000K 4000K 6000K	>80	85lm/W
		HY-DL-06	White	5W,7W,12W	Die cast Aluminum	AC85-265V; 50/60Hz; constant current, isolated power, with fuse and piezoresistor	Ø100xH55 (mm) Beam Angle 60°	80mm	variety for your choose	3000K 4000K 6000K	>80	85lm/W
Panel Light												
Panel Light		HY-PL-01	white	18W	Die cast Aluminum	AC85-265V; 50/60Hz; constant current, isolated power	Ø220mm Beam Angle120°	Ø207mm	variety for your choose	3000K 4000K 6000K	>70	85lm/W